

DVS Extract Air Valves



DESCRIPTION

The DVS range of high quality extract air valves are constructed from steel spinings protected by a gloss white (RAL9010) powder coated finish. The valve body is fitted with a cellular foam sealing gasket and all units are supplied with a plated steel mounting subframe. Air flow adjustment is achieved by rotating the central core inwards or outwards on it's spindle, a locking nut arrangement is provided to set the desired position.

APPLICATION

DVS steel extract air valves provide a clean, attractive and cost effective way of extracting stale air from toilets, bathrooms, cleaners cupboards etc. Air valves are best used in air distribution systems handling relativley small air volumes. The DVS air valve is designed for extract applications.

Type	Size	Volume (l/s)	10	20	30	40	50	60	80	100	120
DVS	100	Ps (Pa)	10	38	75	87	-	-	-	-	-
		dBA	\	22	36	40	-	-	-	-	-
	125	Ps (Pa)	-	30	70	84	110	-	-	-	-
		dBA	-	\	30	33	38	-	-	-	-
	150	Ps (Pa)	-	20	44	63	110	120	-	-	-
		dBA	-	\	25	30	38	40	-	-	-
	200	Ps (Pa)	-	-	-	7	13	20	45	70	-
		dBA	-	-	-	\	\	\	34	40	-

DVS	Ø080	Ø100	Ø125	Ø150	Ø160	Ø200
A	115	138	164	202	211	248
B	61.5	75	99	119	129	157
C	42	40	46	50	54	63
D	105	125	150	175	185	225
E	79	99	124	149	159	199
F	77.5	97.5	122.5	147.5	157.5	197.5

